

MODEL COMPARISON

880 PROJECTOR

1100 PROJECTOR



YEAR OF MANUFACTURE

2001 - Present

2025

MANUFACTURED REQUIREMENT

ISO 3999:2004E

ISO 3999:2004E

TRANSPORT PACKAGE CERTIFICATE

USA/9296/B(U)-96

USA/9296/B(U)-96

LOCKING MECHANISM

Vertical lock
assembly

SFIC (Small Format
Interchangeable Core)

MAXIMUM CAPACITY (IR-192)

150 Ci (5.55 TBq)

150 Ci (5.55 TBq)

S-TUBE

Titanium

Titanium

MODEL COMPARISON

880 PROJECTOR



1100 PROJECTOR



DEPLETED URANIUM WEIGHT

34.4 lb (15.6 kg)

34 lb (15.4 kg)

ACTIVITY OF DEPLETED URANIUM SHIELD

5.4 mCi (200 MBq)

6.4 mCi (236.8 MBq)

TRANSPORT PACKAGE CERTIFICATE

USA/9296/B(U)-96

USA/9296/B(U)-96

WARRANTY

1 Year (S Tube)

3 Years (S Tube)

WEIGHT

55 lb (25 kg)

48 lb (22 kg)

DIMENSIONS

13 1/2 in (L) x 6 in
(W) x 9.7 in (H) (with
jacket)

13 in (L) x 6.6 in
(W) x 8 1/2 in (H)