



FEATURES

- Rugged and Reliable
- Nylon holster or optional see-through holster
- Removable rubber sleeve for extra protection
- Water resistant
- Low power technology (600 hour operation)
- LCD Screen can be rotated 180o
- Battery life indicator
- Large display with backlight
- Top alarm indication (Can be operated in holster)
- PC-software with real-time graph
- 1600 data points (Allows retrospective analysis)
- Adaptable user interface
- Earphone output for noisy environments
- Alarm relay output for area monitor applications

DIGITAL SURVEY METER

- Measuring range: 0.01 mR/h to 10 R/h (0.1 μ Sv/h to 100 mSv/h)
- Overload indication: 10 R/h up to 1000 R/h (100 mSv/h up to 10 Sv/h)
- Energy range: 45 keV-1.3MeV
- Energy compensated GM Tube

RATE ALARM

- Two programmable alarm thresholds for dose and dose rate
- Selectable anywhere from 0.01 mR/h to 9999 mR/h
- Audible, visual and vibrating alerts (Earphone optional)

ELECTRONIC PERSONAL DOSIMETER

- Displays accumulated personal dose
- Records mean/max dose rate
- Records accumulated dose
- PC-software for data analysis and instrument configuration (optional)
- Audible, visual and vibrating alerts (Earphone optional)

Specifications	
Radiation Type	Gamma and X-ray
Dimensions	3.8 in x 2.4 in x 1.2 in (96 mm x 61 mm x 31 mm)
Weight	5.64 oz (160 g)
Measuring Range Dose Rate Dose	0.01 mR to 66 R (0.1 μ Sv to 66 mSv) 0.01 mR/h to 10 R/h (0.1 μ Sv/h to 100 mSv/h)
Energy Range	45 keV - 1.3 MeV
Linear Accuracy	+ 10% within measurement range
Power Requirements	600 hour operation depending on mode
Batteries	2 AAA alkaline or rechargeable
Data Management	11600 data points (mean/max.)
Audible Alarm Intensity	>85 dB at a distance of 30 cm
Operating Temperature	-4° F to 122° F (-20° C to 50° C)